

NCR RealPOS 20

POS Terminal

NCR Service and Support

The NCR RealPOS 20 is supported by our global services team and certified NCR RealPartner resellers, offering a complete portfolio of consulting, development, integration, maintenance and support services.

Technical Specifications

- 12.1" Dual Bulb Active Matrix LCD
- SVGA 800x600 resolution
- ELO AccuTouch 5-wire resistive touch screen
- ELO AccuTouch Controller
- 733MHz VIA processor
- 128MB – 384MB memory
- Built-in mono speaker

Connectivity

- Four powered RS-232 (5V/12V)
- One parallel port
- PS/2 keyboard and mouse ports
- Two USB ports
- Two cash drawer ports
- 10/100 Ethernet

Expansion

- 3.5" hard disk drive
- Compact Flash slot
- On-board mini-PCI slot
- External USB CD-ROM

Options

- 3-track wedge MSR
- Integrated/remote 2x20 VFD customer display
- Wall mount

Operating Systems

- MS-DOS 6.2
- Microsoft® Windows® 2000, XPe, XP Pro and CE.NET
- Linux

Remote Peripherals

- 7167 multi-function thermal receipt printer
- 7197 thermal receipt printer
- Standard PC keyboard
- 5932 alphanumeric 'big ticket' keyboard
- 5972 customer display
- 2189 full-size cash drawer
- 2183 mid-size cash drawer
- 2182 and 2184 compact cash drawers
- 5992 Signature Capture "Plus"
- 5993 Advanced Payment Terminal
- 5945 Electronic Payment Terminal
- NCR's family of hand-held, single-window and Bi-optic scanners

Terminal Dimensions without MSR (W x D x H)

- 12.25" (30.8 cm) x 12" (30.5 cm) x 11.25" (28.5 cm)

For more information, visit www.ncr.com, call 866.431.7879, or email retail.contactus@ncr.com.

